

Lp.	Podstawa	Opis i wyliczenia	j.m.	Poszcz	Razem
1	<b>KNR 2-02 1505-07 sufity</b>	Dwukrotne malowanie farbami emulsyjnymi powierzchni wewnętrznych - suchych tynków z gruntowaniem	m <sup>2</sup>		
		5.75*3.21+5.75*11.57+5.75*8.74+6.00*3.00+5.71*8.76+5.71*8.73+5.70*8.75+8.74*5.84+6.10*3.00+14.58*5.77+(3.04+2.67)*8.76+6.02*2.67+5.87*2.96+5.57*5.73	m <sup>2</sup>	571.835	
	<b>ściany</b>	(5.75*2+3.21*2+5.75*2+11.57*2+5.75*2+8.74*2+6.00*2+3.00+5.71*2+8.76*2+5.71*2+8.73*2+5.70*2+8.75*2+8.74*2+5.84*2+6.00*2+3.00+14.58*2+5.77*2+8.76*2+3.04*2+6.02*2+2.67+2.96+5.87*2+5.57*2+5.73)*3.15	m <sup>2</sup>	1064.700	
	<b>otwory</b>	-2.43*2.05*34	m <sup>2</sup>	-169.371	
				<b>RAZEM</b>	<b>1467.164</b>
2	<b>analiza indywidualna</b>	Osuszanie kondygnacji budynku po zalaniu, sufit i ściany	m <sup>2</sup>		
		poz.1	m <sup>2</sup>	1467.164	
				<b>RAZEM</b>	<b>1467.164</b>